E.E. Zimmerman Company/Elroy Turpentine Company P.O. Box 111254 Pittsburgh, PA 15238 (412) 963-0949

MATERIAL SAFETY DATA SHEET

E-Z MURIATIC ACID

EMERGENCY CONTACT: FOR CHEMICAL EMERGENCY - SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT, CALL CHEMTREC AT 1-(800)-424-9300, DAY OR NIGHT.

INDEX HMIS NFPA

4 - Severe Health 3 Health Not Determined 3 - Serious Flammability Flammability 0 Not Determined 2 - Moderate Reactivity Reactivity Not Determined

1 - Slight

0 - Insignificant

Section 2. CHEMICAL IDENTITY

COMPONENTS: CAS No. **OSHA ACGIH** OTHER LIMITS Hydrogen Chloride (30% in Water) 7647-01-0 PEL TLV None

5 ppm 5 ppm ceiling ceiling

Prepared: 5/05

OSHA HAZARD RATING:

This product contains the following toxic chemical(s) subject to Section 313 Title III reporting requirements (40 CFR Part 372).

Hydrogen Chloride

Section 3. PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT:

ca 185 F

MELTING POINT:

ca -60 F

SPECIFIC GRAVITY $(H_20=1)$:

1.15

VAPOR PRESSURE:

ca 25 mmHg (70 F)

VAPOR DENSITY (Air=1):

Not determined

SOLUBILITY IN WATER:

Soluble

APPEARANCE AND ODOR:

Light yellow fuming liquid with pungent odor and sour taste.

Section 4. FIRE AND EXPLOSION HAZARD DATA

FLASH POINT/METHOD: **AUTOIGNITION TEMP:** Not determined None

FLAMMABILITY LIMITS IN AIR:

LEL: N/A UEL: N/A

EXTINGUISHING MEDIA:

Non-flammable. Use methods appropriate for surroundings.

Page 1 of 3

Firefighters should wear self contained breathing apparatus if there is danger of leakage.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Contact with metals such as iron will produce flammable hydrogen gas.

Section 5.	REACTIVITY	DATA
------------	------------	------

UNSTABLE () STABLE (X)

CONDITIONS TO AVOID:

Liberates significant amounts of hydrogen chloride when heated.

INCOMPATIBILITY (Materials to Avoid):

Metals, metal oxides, hydroxides, amines, carbonates and other alkaline materials.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:

N/A

HAZARDOUS POLYMERIZATION:

() May Occur (X) V

(X) Will Not Occur

CONDITIONS TO AVOID:

N/A

Section 6. HEALTH HAZARD DATA

Prolonged inhalation of hydrogen chloride vapors or mist just above the TLV can damage teeth and irritate the nasal passages. Higher concentrations (50 +ppm) will cause coughing and choking and produce severe irritation and damage of the mucous membranes of the upper respiratory tract. NIOSH has established that 100 ppm is immediately dangerous to life or health (IDLH).

Hydrochloric acid is corrosive and causes burns of human tissue. Ingestion can produce burns of the mouth and digestive tract.

E - Z Muriatic Acid contains less than 0.2% hydrofluoric acid.

PRIMARY ROUTES OF ENTRY:

(X) Inhalation (X) Skin () Eyes () Oral

ACUTE EFFECTS OF OVEREXPOSURE:

Coughing, choking, tissue burns.

CHRONIC EFFECTS OF OVEREXPOSURE:

Unknown

CARCINOGENICITY LISTING:

(No) NTP (No) IARC (No) OSHA (No) Other:

FIRST AID:

Inhalation: Remove to fresh air; restore breathing, if required. Oxygen can be given under proper

supervision. Get medical aid.

Skin: Wash affected areas thoroughly with much water. For gross contact, remove contaminatec

clothing under the safety shower; prolong washing for 15+ minutes.

Eye: Flush thoroughly with running water for 15 minutes. Get medical aid.

Oral: Give limewater or water and milk of magnesia to drink. Do not induce vomiting!

Get medical aid.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

None known.

OTHER HEALTH HAZARDS:

None known.

Section 7. PROTECTION INFORMATION

RESPIRATORY:

Self containing breathing apparatus for emergency use.

VENTILATION:

Adequate general and local exhaust to meet TLV.

EYE AND FACE:

Safety glasses or goggles and/or face shield.

GLOVES:

Impervious gloves (such as neoprene).

OTHER EQUIPMENT:

Rubber apron and boots where appropriate.

Section 8. SPILL, LEAK AND DISPOSAL PROCEDURES

Spill, Leak, or Release:

Remove sources of ignition and supply ventilation. Those involved with clean up of large spills must use full protective clothing, boots and self contained breathing apparatus. Flush with water to holding area and neutralize with caustic or lime.

Waste Disposal:

Flushing of neutralized solution to sewer depends on allowable salt concentrations in effluent. Follow all regulations.

Section 9. OTHER INFORMATION

HAZARDOUS MATERIALS/DANGEROUS GOODS SHIPPING REGULATIONS:

U.S. (49 CFR): Proper Shipping Name: Hydrochloric Acid, Solution

Hazard Class: 8; ID No.: UN 1789: Packaging Group: II

RQ = 5000 lbs.

Container Mode: 55 Gal Drum/15 Gal Drum/5 Gal Pail/Gallon

IATA: Proper Shipping Name: Hydrochloric Acid, Solution

Hazard Class: 8; ID No.: UN 1789; Packaging Group: II

IMDG: Proper Shipping Name: Hydrochloric Acid, Solution

Hazard Class: 8; ID No.: UN 1789; Packaging Group: II

OTHER TRANSPORT INFORMATION

The DOT Transport Information may vary with the container and mode of shipment.

OTHER STORAGE INFORMATION:

Do NOT store in confined areas such as trailers.

E. E. Zimmerman Company/Elroy Turpentine Company believes that the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind, express or implied, and we assume no responsibility for any loss, damage, or expense, direct or consequential, arising out of their use.