

ZEP MANUFACTURING COMPANY P.O. BOX 2015 ATLANTA, GEORGIA 30301

GLOUCESTER CITY SCHOOL GARAGE (379) **RT 17** GLOUCESTER, VA 23061

GAS# 9016-45-9; RTECS# MD905000; OSHA PEL-N/D

# MATERIAL SAFETY DATA SH

AND SAFE HANDLING AND DISPOSAL INFORMATION

05/16/95

**ISSUE DATE: 04/20/93 SUPERSEDES: 07/09/89** 

ZEP REACH PRODUCT NO.: 0925

Hand Cleaner - Liquid

SECTION I - EMERGENCY CONTACTS

**TELEPHONE:** 

(404) 352-1680

BETWEEN 8:00 AM - 5:00 PM (EST)

MEDICAL EMERGENCY:

(404) 435-2973 (404) 351-2952 (404) 432-2873

NON-OFFICE HOURS, WEEKENDS AND HOLIDAYS, PLEASE CALL YOUR

LOCAL POISON CONTROL

TRANSPORTATION EMERGENCY:

(404) 922-0923

CHEMTREC:

1-800-424-9300

**TOLL-FREE - ALL CALLS RECORDED** 

DISTRICT OF COLUMBIA: (202) 483-7616

**ALL CALLS RECORDED** 

ĺ	SECTION II - HAZARDOUS INGREDIENTS	
١	TIV FEECTS	
1	DESIGNATIONS (PPM) (SEE REVER	
I	** LOW ODOR PARAFFINIC SOLVENT ** odorless base oil; dispersol; CAS # 64742-47-8; RTECS # NONE; OSHA 500 CNS CBL IF	RR 30-40
-	PEL-500 ppm.  ** NONYLPHENOXYPOLY(ETHYLENEOXY)ETHANOL ** poly(oxy-1,2-ethanediyl), alpha-(nonylphenyl)-omega-hydroxy; N/D EIR	<5

### SECTION III - HEALTH HAZARD DATA

Special Note: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use (diluted) so long as prescribed safety precautions are practiced.

Acute Effects of Overexposure:

This product is not sufficiently volatile to constitute a significant inhalation hazard. Severe overexposure to concentrated vapor may produce mild central nervous system depression, characterized by headache and stupor. Introduction of solvents, as in aspiration of vomitus fluids, may produce chemical pneumonia. This product can be an eve irritant, Inflammation of eve tissue is characterized by redness, watering, and/or itching.

Chronic Effects of Overexposure:

Skin which is repeatedly defatted by contact with this product may be more susceptible to irritation, infection, or dermatitis. None of the hazardous ingredients are listed as carcinogens by IARC, NTP, & OSHA

Est'd PEL/TLV: Not established

Primary Routes of Entry: Inh.

HMIS Codes: HEALTH 0;FLAM. 0;REACT. 0;PERS. PROTECT. N/A;CHRONIC HAZ. NO

FIRST AID PROCEDURES:

This product is formulated for use on the skin, but it should be rinsed off with water

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting upper and lower lids. Get medical attention at once. Move exposed person to fresh air. If irritation persists, get medical attention promptly.

Inhale:

Ingest: If this product is swallowed, do not induce vomiting. If victim is conscious give plenty of water to drink. Get medical attention at once

SECTION IV - SPECIAL PROTECTION INFORMATION

Protective Clothing: Eve Protection:

Boiling Point (°F):

Respiratory Protection:

No special measures are required. No special measures are required. No special measures are required

Ventilation:

No special measures are required

N/D

**EMULSIFIES** 

SECTION V - PHYSICAL DATA Specific Gravity:

Vapor Density (air = 1): N/D 8.0

SECTION VI - FIRE AND EXPLOSION DATA

Vapor Pressure (mmHg): Evaporation Rate ( = 1): pH (use dilution of ):

N/D N/D N/A

83.5% Solubility in Water: EMULSIFIES pH (concentrate): Appearance and Odor: LIGHT GREEN GEL WITH ALMOND FRAGRANCE

Flash Point (°F) (method used): NONE BELOW 160F (TCC)

Percent Volatile by Volume (%):

Flammable Limits:

LEL N/D UEL N/D

GEL STRUCTURE INHIBITS COMBUSTIBILITY OF SOLVENT

Extinguishing Media: Special Fire Fighting: Unusual Fire Hazards:

None

RECEIVED

MAY 2 3 1995

TRANSPORTATION

# ZEP MANUFACTURING COMPANY

## MATERIAL SAFETY DATA SHEET PAGE 2

Stability: Incompatibility (avoid): Stable

STRONG OXIDIZERS

Polymerization:

Will not occur

Hazardous Decomposition:

May decompose to form toxic/corrosive gases if exposed to high heat

## SECTION VIII - SPILL AND DISPOSAL PROCEDURES

SECTION VII - REACTIVITY DATA

Steps to be Taken in Case Material is Released or Spilled:

Observe safety procedures in section 4 & 9 during clean-up. Absorb spill on inert absorbent material (eg Zep-O-Zorb). Pick up and place residue in a suitable waste container. Wash spill area thoroughly with a detergent solution and rinse well with water. Waste Disposal Method:

Liquid wastes are not permitted in landfills. Product is not considered a hazardous waste under RCRA. Unusable liquid may be absorbed on an inert absorbent material (eg Zep-O-Zorb), drummed, and taken to a chemical or industrial landfill. Pretreatment may be required before landfilling. Consult local, state, or federal agencies for proper disposal in your area.

RCRA Hazardous Waste Numbers: N/A

#### SECTION IX - SPECIAL PRECAUTIONS

Precautions to be Taken When Handling and Storing:

Store tightly closed container in a dry area at temps, between 40-120 degrees F. Keep product out of eyes. Keep out of the reach of children.

#### SECTION X - TRANSPORTATION DATA

DOT Label/Placard: NONE

DOT Proper Shipping Name: NONE

DOT Hazard Class: N/A

DOT I.D. Number: N/A

EPA TSCA Chemical Inventory: ALL INGREDIENTS ARE LISTED

EPA CWA 40CFR Part 117 substance (RQ in a single container): NONE

#### NOTICE

Thank you for your interest in, and use of, Zeo products. Zep Manufacturing Co. is pleased to be of service to you by supplying this Material Safety Data Sheet for your files. Zep Manufacturing is concerned for your health and safety. Zep products can be used safely with proper protective equipment and proper handling practices consistent with label instructions and the MSDS. Before using any Zep product, be sure to read the complete label and the Material Safety

As a further word of caution, Zep wishes to advise that serious accidents have resulted from the misuse of "emptied" containers. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, or other sources of ignition; they may explode or develop harmful vapors and possibly cause injury or death. Clean empty containers by triple rinsing with water or an appropriate solvent. Empty containers must be sent to a drum reconditioner before reuse.

# TERMS AND ABBREVIATIONS USED IN THE MSDS: BY SECTION ALPHABETICALLY:

## SECTION II: HAZARDOUS INGREDIENTS

CAR: Carcinogen - A chemical listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC) or OSHA as a definite or possible human cancer causing agent.

cancer causing agent.

CAS #: Chemical Abstract Services Registry Number - A
universally accepted numbering system for chemical substances.

CBL: Combustible - At temperatures between 100°F and 200°F chemical gives off enough vapor to ignite if a source. of ignition is present as tested with a closed cup tester.

CNS: Central Nervous System depressant reduces the activ-

ity of the brain and spinal cord. COR: Corrosive - Causes irreversible alterations in living

tissue (e.g. burns).
DESIGNATIONS: Chemical and common names of hazardous

ingredients. EIR: Eye Irritant Only - Causes reversible reddening and/or

inflammation of eye tissues.

EXPOSURE LIMITS: The time weighted average (TWA) air-

borne concentration at which most workers can be exposed without any expected adverse effects. Primary sources include ACGIH TLV's, and OSHA PEL's (TWA, STEL and ceiling limits).

ACĞIH. American Conference of Governmental Industrial Hygienists.
CEIUNG: The concentration that should not be exceeded

in the workplace during any part of the working exposure. OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit- A set of time weighted average exposure values, established by OSHA, for a normal 8-hour day and a 40-hour work week.

PPM; Parts per million - unit of measure for exposure

(S) SKIN: Skin contact with substance can contribute to overall exposure.

STEL: Short Term Exposure Limit- Maximum concentration

for a continuous 15-minute exposure period. TLV: Threshold Limit Value - A set of time weighted aver-

age exposure limits, established by the ACGIH, for a normal 8-hour day and a 40-hour work week. FBL: Flammable - At temperatures under 100°F, chemical gives off enough vapor to ignite if a source of ignition is

present as tested with a closed cup tester.

HAZARDOUS INGREDIENTS: Chemical substances determined to be potential health or physical hazards by the criteria established in the OSHA Hazard Communication Standard - 29 CFR 1910.1200

HTX; Highly toxic - the probable lethal dose for 70 kg (150 his, Highly toxic - the probable lethal dose for 70 kg (150 lb.) man and may be approximated as less than 6 teaspoons (2 tablespoons).

IRR: Irritant - Causes reversible effects in living tissues (e.g. inflammation) - primarily skin and eyes.

N/A: Not Applicable - Category is not appropriate for this product.

product.  $N\!\!:\!\!D$ : Not Determined - Insufficient information for a determined result.

mination for this item.

MITCS #: Registry of Toxic Effects of Chemical Substances
- an unreviewed listing of published toxicology data on

SARA: Superfund Amendments and Reauthorization Act -

Section 313 designates chemicals for possible reporting for the Toxics Release Inventory. SEN: Sensitizer - Causes allergic reaction after repeated

exposure.
TOX: Toxic - The probable lethal dose for a 70 kg (150 lb.) man is one ounce (2 tablespoons) or more.

#### SECTION III: HEALTH HAZARD DATA

ACUTE EFFECT: An adverse effect on the human body from

a single exposure with symptoms developing almost immediately after exposure or within a relatively short time. CHRONIC EFFECT; Adverse effects that are most likely to occur from repeated exposure over a long period of time. ESTD PELITLY: This estimated, time-weighted average, exposure limit, developed by using a formula provided by the ACGIH. ACGIH, pertains to airborne concentrations from the product as a whole. This value should serve as guide for providing safe workplace conditions to nearly all workers.

HMIS CODES: Hazardous Material Identification System - a

rating system developed by the National Paint and Coating rating system developed by the National Paint and Coating Association for estimating the hazard potential of a chemical under normal workplace conditions. These risk estimates are indicated by a numerical rating given in each of three hazard areas (Health/Flammability/Reactivity) ranging from a low of zero to a high of 4. A chronic hazard is indicted with a yes. Consult HMIS training guides for Personal Protection letter codes which indicate necessary protective equipment. equipment.

PRIMARY ROUTE OF ENTRY: The way one or more hazardous ingredients may enter the body and cause a general-ized-systemic or specific-organ toxic effect.

ING: Ingestion - A primary route of exposure through

ING: Ingestion - A primary route of exposure through swallowing of material. InH: Inhalation - A primary route of exposure through breathing of vapors.

SKIN: A primary route of exposure through contact with

#### SECTION IV: SPECIAL PROTECTION INFORMATION

Where respiratory protection is recommended, use only MSHA and NIOSH approved respirators and dust masks. MSHA: Mine Salety and Health Administration

NIOSH: National Institute for Occupational Safety and Health.

#### SECTION V: PHYSICAL DATA

EVAPORATION RATE: it refers to the rate of change from the liquid state to the vapor state at ambient temperature and pressure in comparison to a given substance (e.g. water).

pH: A value representing the acidity or alkalinity of an aqueous solution (Acidic pH = 1; Neutral pH = 7; Alkaline

pH = 14)
PERCENT VOLATILE. The percentage of the product (figuid or solid) that will evaporate at 212°F and ambient pressure.
SOLUBILITY IN WATER: A description of the ability of the product to dissolve in water.

#### SECTION VII: REACTIVITY DATA

HAZARDOUS DECOMPOSITION: Breakdown products expected to be produced upon product decomposition or lire.

INCOMPATIBILITY: Material contact and conditions to avoid to prevent hazardous reactions

POLYMERIZATION: Indicates the tendency of the product's molecules to combine in a chemical reaction releasing ex

cess pressure and heal.

STABILITY: Indicates the susceptibility of the product to spontaneously and dangerously decompose.

# SECTION VIII: SPILL AND DISPOSAL PROCEDURES

RCRA WASTE NOS: RCRA (Resource Conservation and Recovery Act) waste codes (40 CFR 261) applicable to the disposal of spilled or unusable product from the original container.

# SECTION X: TRANSPORTATION DATA

CWA; Clean Water Act RQ; Reportable Quantity - The amount of the specific ingredient that. when spilled to the ground and can enter a storm sewer or natural watershed, must be reported to the National Response Center, and other regulatory agencies. TSCA: Toxic Substances Control Act - a federal law requir ing all commercial chemical substances to appear on an inventory maintained by the EPA.

### DISCLAIMER

All statements, technical information and recommendations contained herein are based on available scientific tests or data which we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. Zep assumes no liability or responsibility for loss or damage resulting from the improper use or handling of our products, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the product's label and Material Safety Data Sheet.

(Notice Revised 8/91)