

Battery cleaner & protector

1

ORDER NO: 6113942 RELEASE NO: 002 MSDS NO: 005460

BARNES DISTRIBUTION

Synonyms: BD1070 BD1070-1
MATERIAL SAFETY DATA SHEET

BD1070
0300

-----SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION -----

PRODUCT NUMBER: BD1070

PRODUCT NAME: PRO KLEEN BATTERY CLEANER & PROTECTOR

DATE OF PREPARATION: MAY 10, 2012

HMIS CODES:

HEALTH 2
FLAMMABILITY 2
REACTIVITY 0

MANUFACTURER'S NAME:

MFG. FOR: BARNES DISTRIBUTION
1301 EAST 9TH ST., SUITE 700
CLEVELAND, OH 44114-1824

TELEPHONE NUMBERS AND WEBSITES:

PRODUCT INFORMATION: (866) 438-6767

REGULATORY INFORMATION: (216) 566-2902

MEDICAL EMERGENCY: (303) 623-5716

TRANSPORTATION EMERGENCY: (800) 424-9300

FOR CHEMICAL EMERGENCY ONLY (SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT)

-----SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS -----

% BY WT	CAS NO.	INGREDIENT	UNITS	VAPOR PRESSURE
5	74-98-6	PROPANE ACGIH TLV: 2500 PPM OSHA PEL: 1000 PPM		760 MM
2	106-97-8	BUTANE ACGIH TLV: 800 PPM OSHA PEL: 800 PPM		760 MM
10	64742-89-8	LT. ALIPHATIC HYDROCARBON SOLVENT ACGIH TLV: 100 PPM OSHA PEL: 100 PPM		53 MM

ORDER NO: 6113942 RELEASE NO: 002 MSDS NO: 005460

BARNES DISTRIBUTION

10	8009-03-8	PETROLATUM	
		ACGIH TLV: 5 MG/M3 AS MIST	
		OSHA PEL: 5 MG/M3 AS MIST	
14	108-88-3	TOLUENE	22 MM
		ACGIH TLV: 20 PPM	
		OSHA PEL: 100 PPM (SKIN)	
		OSHA PEL: 150 PPM (SKIN) STEL	

-----SECTION 3 - HAZARDS IDENTIFICATION -----

ROUTES OF EXPOSURE:

INHALATION OF VAPOR OR SPRAY MIST.

EYE OR SKIN CONTACT WITH THE PRODUCT, VAPOR OR SPRAY MIST.

EFFECTS OF OVEREXPOSURE:

EYES: IRRITATION.

SKIN: PROLONGED OR REPEATED EXPOSURE MAY CAUSE IRRITATION.

INHALATION:

IRRITATION OF THE UPPER RESPIRATORY SYSTEM.

MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS AND POSSIBLY DEATH.

PROLONGED OVEREXPOSURE TO SOLVENT INGREDIENTS IN SECTION 2 MAY CAUSE ADVERSE EFFECTS TO THE LIVER, URINARY, CARDIOVASCULAR AND REPRODUCTIVE SYSTEMS.

SIGNS AND SYMPTOMS OF OVEREXPOSURE:

HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MISTS.

REDNESS AND ITCHING OR BURNING SENSATION MAY INDICATE EYE OR EXCESSIVE SKIN EXPOSURE.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: NONE GENERALLY RECOGNIZED.

CANCER INFORMATION:

FOR COMPLETE DISCUSSION OF TOXICOLOGY DATA REFER TO SECTION 11.

-----SECTION 4 - FIRST AID MEASURES -----

EYES:

FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.
GET MEDICAL ATTENTION.

SKIN:

WASH AFFECTED AREA THOROUGHLY WITH SOAP AND WATER.
REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE RE-USE.

ORDER NO: 6113942 RELEASE NO: 002 MSDS NO: 005460

BARNES DISTRIBUTION

INHALATION:

IF AFFECTED, REMOVE FROM EXPOSURE. RESTORE BREATHING.
KEEP WARM AND QUIET.

INGESTION:

DO NOT INDUCE VOMITING.
GET MEDICAL ATTENTION IMMEDIATELY.

-----SECTION 5 - FIRE FIGHTING MEASURES -----

FLASH POINT: PROPELLANT <0 F

LEL: 1.0

UEL: 9.5

EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CLOSED CONTAINERS MAY EXPLODE (DUE TO THE BUILD-UP OF PRESSURE) WHEN EXPOSED TO EXTREME HEAT.

APPLICATION TO HOT SURFACES REQUIRES SPECIAL PRECAUTIONS.

DURING EMERGENCY CONDITIONS OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. OBTAIN MEDICAL ATTENTION.

SPECIAL FIRE FIGHTING PROCEDURES:

FULL PROTECTIVE EQUIPMENT INCLUDING SELF-CONTAINED BREATHING APPARATUS SHOULD BE USED.

WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

-----SECTION 6 - ACCIDENTAL RELEASE MEASURES -----

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

REMOVE ALL SOURCES OF IGNITION. VENTILATE THE AREA.
REMOVE WITH INERT ABSORBENT.

-----SECTION 7 - HANDLING AND STORAGE -----

STORAGE CATEGORY: NOT AVAILABLE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. VAPORS WILL ACCUMULATE READILY AND MAY IGNITE EXPLOSIVELY.

ORDER NO: 6113942 RELEASE NO: 002 MSDS NO: 005460

B A R N E S D I S T R I B U T I O N

DURING USE AND UNTIL ALL VAPORS ARE GONE:

KEEP AREA VENTILATED - DO NOT SMOKE - EXTINGUISH ALL FLAMES, PILOT LIGHTS, AND HEATERS - TURN OFF STOVES, ELECTRIC TOOLS AND APPLIANCES, AND ANY OTHER SOURCES OF IGNITION.

CONSULT NFPA CODE. USE APPROVED BONDING AND GROUNDING PROCEDURES.

CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE, OR EXPOSE TO TEMPERATURE ABOVE 120F. HEAT FROM SUNLIGHT, RADIATORS, STOVES, HOT WATER, AND OTHER HEAT SOURCES COULD CAUSE CONTAINER TO BURST. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

-----SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION -----

PRECAUTIONS TO BE TAKEN IN USE:

USE ONLY WITH ADEQUATE VENTILATION.

AVOID CONTACT WITH SKIN AND EYES. AVOID BREATHING VAPOR AND SPRAY MIST. WASH HANDS AFTER USING.

VENTILATION:

LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE TO MATERIALS IN SECTION 2 IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

REFER TO OSHA STANDARDS 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION:

IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, WEAR A PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION AGAINST MATERIALS IN SECTION 2.

PROTECTIVE GLOVES:

NONE REQUIRED FOR NORMAL APPLICATION OF AEROSOL PRODUCTS WHERE MINIMAL SKIN CONTACT IS EXPECTED. FOR LONG OR REPEATED CONTACT, WEAR CHEMICAL RESISTANT GLOVES.

EYE PROTECTION: WEAR SAFETY SPECTACLES WITH UNPERFORATED SIDESHIELDS.

OTHER PRECAUTIONS:

INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

-----SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -----

PRODUCT WEIGHT:

7.26 LB/GAL

869 G/L

SPECIFIC GRAVITY: 0.87

BOILING POINT:

<0 - 238 F

ORDER NO: 6113942 RELEASE NO: 002 MSDS NO.: 005460

BARNES DISTRIBUTION

<-18 - 114 C

MELTING POINT: NOT AVAILABLE

VOLATILE VOLUME: 88 %

EVAPORATION RATE: FASTER THAN ETHER

VAPOR DENSITY: HEAVIER THAN AIR

SOLUBILITY IN WATER: N.A.

pH: 7.0

VOLATILE ORGANIC COMPOUNDS (VOC THEORETICAL - AS PACKAGED):
VOLATILE WEIGHT 32.17% LESS WATER AND FEDERALLY EXEMPT SOLVENTS

-----SECTION 10 - STABILITY AND REACTIVITY -----

STABILITY: STABLE

CONDITIONS TO AVOID: NONE KNOWN.

INCOMPATIBILITY: NONE KNOWN.

HAZARDOUS DECOMPOSITION PRODUCTS:
BY FIRE: CARBON DIOXIDE, CARBON MONOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

-----SECTION 11 - TOXICOLOGICAL INFORMATION -----

CHRONIC HEALTH HAZARDS:
NO INGREDIENT IN THIS PRODUCT IS AN IARC, NTP OR OSHA LISTED CARCINOGEN.

REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH
PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.

TOXICOLOGY DATA:

CAS NO.	INGREDIENT NAME
74-98-6	PROPANE LC50 RAT 4HR: NOT AVAILABLE LD50 RAT: NOT AVAILABLE
106-97-8	BUTANE LC50 RAT 4HR: NOT AVAILABLE LD50 RAT: NOT AVAILABLE
64742-89-8	LT. ALIPHATIC HYDROCARBON SOLVENT

ORDER NO: 6113942 RELEASE NO: 002 MSDS NO: 005460

BARNES DISTRIBUTION
LC50 RAT 4HR: NOT AVAILABLE
LD50 RAT: NOT AVAILABLE

8009-03-8 PETROLATUM
LC50 RAT 4HR: NOT AVAILABLE
LD50 RAT: NOT AVAILABLE

108-88-3 TOLUENE
LC50 RAT 4HR: 4000 PPM
LD50 RAT: 5000 MG/KG

-----SECTION 12 - ECOLOGICAL INFORMATION -----

ECOTOXICOLOGICAL INFORMATION: NO DATA AVAILABLE.

-----SECTION 13 - DISPOSAL CONSIDERATIONS -----

WASTE DISPOSAL METHOD:
WASTE FROM THIS PRODUCT MAY BE HAZARDOUS AS DEFINED UNDER THE RESOURCE
CONSERVATION AND RECOVERY ACT (RCRA) 40 CFR 261.

WASTE MUST BE TESTED FOR IGNITABILITY TO DETERMINE THE APPLICABLE EPA HAZARDOUS
WASTE NUMBERS.

DO NOT INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF IN ACCORDANCE WITH
FEDERAL, STATE/PROVINCIAL, AND LOCAL REGULATIONS REGARDING POLLUTION.

-----SECTION 14 - TRANSPORT INFORMATION -----

Multi-modal shipping descriptions are provided for informational purposes and
do not consider container sizes. The presence of a shipping description for a
particular mode of transport (ocean, air, etc.), does not indicate that the
product is packaged suitably for that mode of transport. All packaging must be
reviewed for suitability prior to shipment, and compliance with the applicable
regulations is the sole responsibility of the person offering the product for
transport.

US GROUND (DOT):
MAY BE CLASSIFIED AS LTD. QTY. OR ORM-D
UN1950, AEROSOLS, 2.1, LIMITED QUANTITY, (ERG#126)

CANADA (TDG):
MAY BE CLASSIFIED AS LTD. QTY. OR ORM-D
UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, (ERG#126)

IMO:
MAY BE SHIPPED AS LIMITED QUANTITY
UN1950, AEROSOLS, CLASS 2.1, LIMITED QUANTITY, EMS F-D, S-U, ADR(D)

IATA/ICAO
UN1950, AEROSOLS, FLAMMABLE, 2.1, LIMITED QUANTITY

ORDER NO: 6113942 RELEASE NO: 002 MSDS NO: .005460

BARNES DISTRIBUTION

-----SECTION 15 - REGULATORY INFORMATION -----

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION:

CAS NO.	CHEMICAL/COMPOUND	% BY WT	% ELEMENT
108-88-3	TOLUENE	14	

CALIFORNIA PROPOSITION 65:

WARNING:

THIS PRODUCT CONTAINS CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

TSCA CERTIFICATION:

ALL CHEMICALS IN THIS PRODUCT ARE LISTED, OR ARE EXEMPT FROM LISTING, ON THE TSCA INVENTORY.

CANADA WHMIS CLASS CODES:

CLASS B- DIVISION 5- FLAMMABLE AEROSOL

CLASS D- DIVISION 2-SUBDIVISION A- VERY TOXIC MATERIAL

-----SECTION 16 - OTHER INFORMATION -----

THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CANADIAN CONTROLLED PRODUCTS REGULATIONS (CPR) AND THE MSDS CONTAINS ALL OF THE INFORMATION REQUIRED BY THE CPR.

THE ABOVE INFORMATION PERTAINS TO THIS PRODUCT AS CURRENTLY FORMULATED, AND IS BASED ON THE INFORMATION AVAILABLE AT THIS TIME. ADDITION OF REDUCERS OR OTHER ADDITIVES TO THIS PRODUCT MAY SUBSTANTIALLY ALTER THE COMPOSITION AND HAZARDS OF THE PRODUCT. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.

GA...

...

...