

**Material Safety Data Sheet**  
 May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements.

**U.S. Department of Labor**  
 Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072



**IDENTITY (As Used on Label and List)**  
 Non-etching, Non-burning Primer

*Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.*

**Section I**

Manufacturer's Name Tammy Taylor Nails	Emergency Telephone Number 407 240 8340
Address (Number, Street, City, State, and ZIP Code) 18007-E Sky Park Circle Irvine, CA 92714	Telephone Number for Information 714 250 9287
	Date Prepared 11-21-90
	Signature of Preparer (optional)

**Section II — Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Ethyl Acetate		400ppm		
Modified Acrylic Acid		Not established		
Isopropyl Alcohol		400ppm		
Methyl Alcohol		200ppm		

**Section III — Physical/Chemical Characteristics**

Boiling Point 167°F	Specific Gravity (H <sub>2</sub> O = 1) 0.8
Vapor Pressure (mm Hg.) 42mm. Hg	Melting Point
Vapor Density (AIR = 1) 1.6	Evaporation Rate (Butyl Acetate = 1) 3.1
Solubility in Water complete	
Appearance and Odor Clear liquid, slightly acrid odor.	

**Section IV — Fire and Explosion Hazard Data**

Flash Point (Method Used) 24°F. Tag Closed Cap ASTM D56	Flammable Limits	LEL 3.3%	UEL 19.0%
Extinguishing Media water spray, foam, carbon dioxide, dry chemical			
Special Fire Fighting Procedures none			
Unusual Fire and Explosion Hazards none			

**Section V — Reactivity Data**

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (Materials to Avoid)  
Strong, oxidizing agents

Hazardous Decomposition or Byproducts  
Oxides of carbon

Hazardous Polymerization	May Occur	X	Conditions to Avoid heat, sparks, fires
	Will Not Occur		

**Section VI — Health Hazard Data**

Route(s) of Entry:                      Inhalation?                      Skin?                      Ingestion?

Health Hazards (Acute and Chronic)

Carcinogenicity:                      NTP?                      IARC Monographs?                      OSHA Regulated?  
NO

**Signs and Symptoms of Exposure**

High vapor concentration will irritate eyes, nose and throat. Liquid could cause eye and skin irritation. Absorption through the skin may cause systemic illness with nausea and vomiting. Ingestion may cause inebriation. Breathing vapors may cause drowsiness.

**Emergency and First Aid Procedures**

INHALATION: Move exposed person to fresh air. If symptoms are apparent consult a physician promptly. EYE AND SKIN CONTACT: Immediately flush eyes with copious amounts of water and continue flushing for 15 minutes, occasionally lifting eyelids. Get medical attention immediately. Promptly wash the contaminated skin with soap or mild detergent and water. Remove contaminated clothing. Get medical attention. INGESTION: DO NOT induce vomiting. Give person large quantities of water or milk if conscious. Seek medical attention immediately.

**Section VII — Precautions for Safe Handling and Use**

**Steps to Be Taken in Case Material is Released or Spilled**

Wear approved respirator, impervious clothing and boots. Dike and neutralize spill with dilute caustic. Flush to contaminated sewer system with a large excess of water. Keep spill out of municipal and open bodies of water.

**Waste Disposal Method**

Incinerate in approved equipment. Absorbed material should be landfilled in closed containers according to local, state and federal regulations.

**Precautions to Be Taken in Handling and Storing**

store in a cool, dark place.

**Other Precautions**

Precautionary Labeling: Warning: Flammable, Keep away from heat, sparks, and open flames. Keep container closed. Use with adequate ventilation.

**Section VIII — Control Measures**

**Respiratory Protection (Specify Type)**

organic vapor cartridge respirator

Ventilation	Local Exhaust recommended	Special
	Mechanical (General)	Other

Protective Gloves: impervious                      Eye Protection: goggles

Other Protective Clothing or Equipment: Clothing to prevent repeated or prolonged skin contact.

Work/Hygienic Practices: Wipe contaminated equipment with alcohol after use, wash skin with soap and water if contact occurs.