

Page : 1

Revised edition no : 2

Date: 4 / 28 / 2008

Supersedes: 2 / 10 / 2008

Superbond Primer

NSI-120



C: Corrosive

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Trade name : Superbond Primer

Identification of the product : Liquid.

Type of product : Adhesives intensifier. **Use** : For professional use only.

Company identification : NAIL SYSTEMS INTERNATIONAL

2 Union Hill Road

W. Conshohocken, PA 19428 UNITED STATES

Tel. (610) 825-1524

Emergency phone nr : Infotrac (800) 535-5053 - Outside USA (352) 323-3500

2 HAZARDS IDENTIFICATION

Risk Phrases : Corrosive to eyes, respiratory system and skin.

Harmful in contact with skin and if swallowed.

Primary route of exposure

Symptoms relating to use

- Inhalation

: Vapours inhalation. Skin and eyes contact.

: Cough. Sore throat. Chest pain. Shortness of breath. Corrosive to respiratory system.

- Skin contact : Redness, pain. May produce skin irritation, blistering, ulcers, and deep scarring.

- Eye contact : Redness, pain. Blurred vision. Burning sensation.

Risk of serious damage to eyes. May cause destruction of eye tissue.

- Ingestion : Chest pain. Burning sensation. Abdominal pain, nausea.

May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal

tract.

Swallowing a small quantity of this material will result in serious health hazard. Must

not come into contact with food or be consumed.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Components : This product is hazardous.

 Substance name
 Contents
 CAS No
 EC No
 Annex No
 Classification

 METHACRYLIC ACID
 :
 100 %
 79-41-4
 201-204-4
 607-088-00-5
 Xn; R21/22 C; R35

4 FIRST AID MEASURES

First aid measures

- Inhalation : Assure fresh air breathing. Allow the victim to rest. If breathing is difficult, give

oxygen. Seek medical advice.

- Skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water,

followed by warm water rinse.

Seek medical attention if burns develop.

NAIL SYSTEMS INTERNATIONAL

In case of emergency: Infotrac (800) 535-5053 - Outside USA (352) 323-3500

2 Union Hill Road W. Conshohocken, PA 19428 UNITED STATES



Page : 2

Revised edition no : 2

Date : 4 / 28 / 2008

Supersedes: 2 / 10 / 2008

Superbond Primer

NSI-120

4 FIRST AID MEASURES (continued)

- Eye contact : In case of eye contact, immediately rinse with clean water for 10-15 minutes.

Retract eyelids often.

Contact ophthalmologist immediately.

- Ingestion : If swallowed, rinse mouth with water (only if the person is conscious). Do not induce

vomiting because of corrosive effects.

Call a physician immediately.

Other information : In all case : Obtain medical attention.

5 FIRE-FIGHTING MEASURES

Flammable class : Combustible.

Specific hazards : High temperature may liberate dangerous gases. Corrosive vapours.

Hazardous combustion products

: Carbon dioxide. Carbon monoxide.

Extinguishing media : Sand. Powder. Dry chemical. Carbon dioxide.

Apply aqueous extinguishing media carefully. May release heat.

Surrounding fires : Use water spray or fog for cooling exposed containers.

Protection against fire : Do not enter fire area without proper protective equipment, including respiratory

protection.

Special procedures : Exercise caution when fighting any chemical fire.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions : Spill should be handled by trained cleaning personnel properly equipped with

respiratory and eye protection.

General precautions : Eliminate every possible source of ignition.

Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if product enters

sewers or public waters.

Clean up methods : Collect spills and put it into appropriated container. Use non-corrodable disposal

containers.

7 HANDLING AND STORAGE

General : Store and handle as thought always a serious health hazard exists.

Precautions in handling and storage : Good ventilation of the workplace required. Vapours may cause painful eye

irritation.

Storage : Store in dry, well-ventilated area. Keep container closed when not in use.

Handling : Ensure prompt removal from eyes, skin and clothing. For even minor contact,

immediately remove contaminated clothing. Wash skin thoroughly with mild soap

and water.

Wash hands and other exposed areas with mild soap and water before eat, drink or

smoke and when leaving work.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection

equipment is recommended.

- Hand protection : Wear suitable gloves resistant to chemical penetration.

- Skin protection : If skin contact or contamination of clothing is likely, protective clothing should be

NAIL SYSTEMS INTERNATIONAL

In case of emergency: Infotrac (800) 535-5053 - Outside USA (352) 323-3500

2 Union Hill Road W. Conshohocken, PA 19428 UNITED STATES



Page : 3

Revised edition no : 2

Date : 4 / 28 / 2008

Supersedes: 2 / 10 / 2008

Superbond Primer

NSI-120

8 EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

worn.

- Eye protection : Chemical goggles or face shield with safety glasses.

- Ingestion : When using, do not eat, drink or smoke.

Industrial hygiene : Provide local exhaust or general room ventilation to minimize dust and/or vapour

concentrations.

Emergency eye wash fountains and safety showers should be available in the

immediate vicinity of any potential exposure.

Occupational Exposure Limits : Methacrylic acid : TLV© -TWA [mg/m³] : 70

Methacrylic acid: TLV©-TWA [ppm]: 20

9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C : Liquid. Colour : Colourless. Odour : Characteristic. pH value : 2.0 - 2.2 Boiling point [°C] : 163 Density : 1.015 Vapour pressure [20°C] : 1 mm Hg Solubility in water : Insoluble.

Flash point [°C] : 65
Flammability range [vol% in air] : 1.6 - 8.7
Auto-ignition temperature [°C] : 400
Evaporation rate (ether=1) : < 1

10 STABILITY AND REACTIVITY

Stability and reactivity : This product is stable with an appropriate level of inhibitor, but reactive (unstable)

without.

Hazardous decomposition products : Thermal decomposition generates : Corrosive vapours.

Hazardous polymerization : Hazardous polymerization may occur if exposure to fire conditions.

Hazardous properties : Incompatible with : Peroxides. Strong acids. Strong oxidizers. Amines. etc...

Conditions to avoid : Extremely high or low temperatures.

11 TOXICOLOGICAL INFORMATION

Toxicity information

Rat oral LD50 [mg/kg] : 1060

Dermal irritation (rabbit) : Severe skin irritant. Causes burns.

Eyes irritation (rabbit) : Severe eye irritant. Causes burns. May cause destruction of eye tissue.

12 ECOLOGICAL INFORMATION

Ecological effects information : No data available.

NAIL SYSTEMS INTERNATIONAL

In case of emergency: Infotrac (800) 535-5053 - Outside USA (352) 323-3500

2 Union Hill Road W. Conshohocken, PA 19428 UNITED STATES



Page : 4

Revised edition no : 2

Date: 4 / 28 / 2008

Supersedes : 2 / 10 / 2008

Superbond Primer

NSI-120

13 DISPOSAL CONSIDERATIONS

General : Avoid release to the environment.

Dispose of this material and its container at hazardous or special waste collection

point.

Dispose in a safe manner in accordance with local/national regulations.

14 TRANSPORT INFORMATION

Proper shipping name : UN2531 METHACRYLIC ACID, STABILIZED, 8, II

UN No. : 2531 **H.l. nr** : 89

Land transport

ADR/RID : Class : 8

Group: II

Labelling ADR



Sea transport

- IMO-IMDG code : Class 8
- IMO Packing group : II

Air transport

- IATA - Class or division : 8 - IATA Packing group : II

15 REGULATORY INFORMATION

Symbol(s) : C : Corrosive

R Phrase(s) : R21/22 : Harmful in contact with skin and if swallowed.

R35: Causes severe burns.

S Phrase(s) : S1/2 : Keep locked up and out of reach of children.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

S36/37/39: Wear suitable protective clothing, gloves and eye/face protection. S45: In case of accident or if you feel unwell, seek medical advice immediately (

show the label when possible).

The contents and format of this SDS are in accordance with REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

For EU Regulatory Inquiries please contact: FSE International NV/SA 9 Rue du Moniteur-B-1000 Brussels, Belgium 011 322 277 07 70

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.



Page : 5
Revised edition no : 2

Date: 4 / 28 / 2008

Supersedes: 2 / 10 / 2008

Superbond Primer

NSI-120

End of document