

PLASTI-KOTE -- AEROSOL SPRAY PAINT FLUORESCENT, FL-7 GREEN
MATERIAL SAFETY DATA SHEET
NSN: 801000N027321
Manufacturer's CAGE: 07708
Part No. Indicator: A
Part Number/Trade Name: AEROSOL SPRAY PAINT FLUORESCENT, FL-7 GREEN

=====
General Information
=====

Company's Name: PLASTI-KOTE CO INC
Company's Street: 1000 LAKE ROAD
Company's City: MEDINA
Company's State: OH
Company's Country: US
Company's Zip Code: 44256
Company's Emerg Ph #: 216-725-4511
Company's Info Ph #: 216-725-4511
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 002
Status: SMJ
Date MSDS Prepared: 31JAN90
Safety Data Review Date: 28FEB92
MSDS Serial Number: BMTHG
Hazard Characteristic Code: F1

=====
Ingredients/Identity Information
=====

Proprietary: NO
Ingredient: SOLVENT NAPHTHA (PETROLEUM) LIGHT ALIPHATIC; (ALIPHATIC
HYDROCARBON). VP:38 @ 20C.
Ingredient Sequence Number: 01
Percent: 30-35
NIOSH (RTECS) Number: 1004249NP
CAS Number: 64742-89-8
OSHA PEL: 300 MG/M3 (MFR)
ACGIH TLV: 300 MG/M3 (MFR)
Other Recommended Limit: 500 PPM (MFR)

Proprietary: NO
Ingredient: MINERAL SPIRITS. VP:2 @ 20C.
Ingredient Sequence Number: 02
Percent: 5-10
NIOSH (RTECS) Number: 1005956MS
CAS Number: 64742-88-7
OSHA PEL: 100 MG/M3 (MFR)
ACGIH TLV: 350 MG/M3 (MFR)

Proprietary: NO
Ingredient: TOLUENE (SARA III)
Ingredient Sequence Number: 03
Percent: 5-10
NIOSH (RTECS) Number: XS5250000
CAS Number: 108-88-3
OSHA PEL: 200 PPM/150 STEL
ACGIH TLV: 50 PPM; 9293
Other Recommended Limit: 200PPM;375MG/M3 (MFR)

Proprietary: NO
Ingredient: XYLENE. VP:5.1 @ 20C.
Ingredient Sequence Number: 04
Percent: 5-10
NIOSH (RTECS) Number: ZE2100000
CAS Number: 1330-20-7

OSHA PEL: 100 PPM;150 PPM STEL
ACGIH TLV: 100 PPM;150 PPM STEL
Other Recommended Limit: 435 MG/M3 (MFR)

Proprietary: NO
Ingredient: PROPANE, 2-METHYL; (ISOBUTANE MIXTURE) (PROPELLANT)
Ingredient Sequence Number: 05
Percent: 20
NIOSH (RTECS) Number: TZ4300000
CAS Number: 75-28-5
OSHA PEL: NOT APPLICABLE
ACGIH TLV: NOT APPLICABLE

Proprietary: NO
Ingredient: NON HAZARDOUS INGREDIENTS
Ingredient Sequence Number: 06
Percent: 25-27
NIOSH (RTECS) Number: 1000314NH
OSHA PEL: NOT APPLICABLE
ACGIH TLV: NOT APPLICABLE
=====

Physical/Chemical Characteristics

=====

Appearance And Odor: TYPICAL SOLVENT PAINT.
Melting Point: 1500F,816C
Vapor Pressure (MM Hg/70 F): SEE INGS
Vapor Density (Air=1): HVR/AIR
Specific Gravity: <1 (H*20=1)
Evaporation Rate And Ref: SEE SUPP DATA
Solubility In Water: SLIGHT TO MODERATE.
Percent Volatiles By Volume: 85-90
=====

Fire and Explosion Hazard Data

=====

Flash Point: SUPP DATA
Lower Explosive Limit: 1%
Extinguishing Media: "ALCOHOL" FOAM, CO*2, DRY CHEMICAL.
Special Fire Fighting Proc: WEAR NIOSH/MSHA APPRVD SCBA & FULL PROT EQUIP (FP N). H*2O SPRAY MAY BE INEFT. H*2O MAY BE USED TO COOL CLSD CNTNRS TO PVNT PRESS BUILD-UP & POSS AUTO- (SUPDAT)
Unusual Fire And Expl Hazrds: CLSD CNTNRS MAY EXPLODE &/OR AUTOIGNITE WHEN EXPOSED TO EXTREME HEAT. VAPS ARE HVR/AIR & MAY TRAVEL ALONG GROUND/MAY BE MOVED BY VENT & IGNITED BY PILOT(SUPDAT)
=====

Reactivity Data

=====

Stability: YES
Cond To Avoid (Stability): HEAT, SPARKS & OPEN FLAME.
Materials To Avoid: AVOID CONTACT W/STRONG OXIDIZING AGENTS & HEAT.
Hazardous Decomp Products: MAY FORM TOXIC MATLS, CO*2/CO, VARIOUS HYDROCARBONS, NITROGEN COMPOUNDS, ETC WHEN BURNED.
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): NOT RELEVANT
=====

Health Hazard Data

=====

LD50-LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: ACUTE:INHAL:EXCESS INHAL OF VAPS CAN CAUSE NASAL & RESP IRRIT, DIZZ, WEAK, FATG, NAUS, HDCH, POSS UNCON & EVEN ASPHY. EYE:CAN CAUSE SEV IRRIT, REDNESS, TEARING, BLURRED VISION. INGEST:CAN CAUSE GI IRRIT, NAUS, VOMIT, DIARR. SKIN:CAN CAUSE IRRIT FOR SOME PERSONS.
=====

CHRONIC:REPORTS HAVE ASSOC RPTD & PRLNG (EFTS OF OVEREXP)

Carcinogenicity - NTP: NO

Carcinogenicity - IARC: NO

Carcinogenicity - OSHA: NO

Explanation Carcinogenicity: NOT RELEVANT

Signs/Symptoms Of Overexp: HLTH HAZ:OCCUP OVEREXP TO SOLVS W/PERM BRAIN & NERV SYS DMG. SEVERE OVEREXP IN LAB ANIMALS HAS ALSO CAUSED LIVER ABNORM & DMG TO KIDNEYS, LUNGS & SPLEEN, HEART & ADRENALS. INTENT MISUSE BY DELIB CONC & INHALING CONTENTS MAY BE HARMFUL/FATAL.

Med Cond Aggravated By Exp: CAN CAUSE ALLERGIC RESPIRATORY &/OR SKIN REACTION.

Emergency/First Aid Proc: INHAL:REMOVE INDIVIDUAL TO FRESH AIR. IF BRTHG DFCLT, ADMIN O*2. IF BRTHG STOPPED, GIVE ARTF RESP & SEE MD. EYES: FLUSH W/H*20 FOR @ LST 15 MIN WHILE OCCAS HOLDING EYELIDS OPEN. GET MD. INGEST:DO NOT INDUCE VOMIT (ASPIR OF MATL INTO LUNGS CAN CAUSE CHEM PNEUM, WHICH CAN BE FATAL). KEEP PERS WARM, QUIET & GET MD/POIS CTL CTR. SKIN:WASH W/SOAP & H*20/VARIOUS HAND CLEANERS & WASH CLTHG BEFORE RE-USE.

Precautions for Safe Handling and Use

Steps If Matl Released/Spill: ELIMINATE ALL IGNITION SOURCES. VENTILATE AREA. ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL & TRANSFER TO CLOSED CONTAINER.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Method: MATERIAL COLLECTED ON ABSORBENT MATERIAL MAY BE DEPOSITED IN POSTED TOXIC SUBSTANCE. LANDFILL I/A/W LOCAL, STATE & FEDERAL REGULATIONS.

Precautions-Handling/Storing: DO NOT STORE IN AREAS ABOVE 120F, OR IN DIRECT SUNLIGHT/NEAR HEAT/OPEN FLAMES. DO NOT PUNCTURE/INCINERATE.

Other Precautions: STORE LARGE QUANTITIES IN BUILDINGS PROTECTED FOR STORAGE OF NFPA CLASS IC FLAMMABLE LIQUIDS. AS W/ALL CHEMICALS, MINIMIZE PERSONAL CONTACT & BREATHING OF VAPORS.

Control Measures

Respiratory Protection: FOR CASUAL/OCCAS USE:TO AVOID BRTHG VAPS/SPRAY MIST, OPEN WINDOWS & DOORS/USE OTHER MEANS TO ENSURE FRESH AIR ENTRY DURING APPLIC & DRYING. IF YOU EXPER EYE WATERING, HDCHS/DIZZ, INCR FRESH AIR, WEAR NIOSH/MSHA APPRVD RESP PROT/LEAVE AREA.

Ventilation: FOR REGULAR/CONTINUOUS USE:PROVIDE SUFFICIENT MECH (GEN) &/OR LOC EXHST VENT TO MAINT EXPOS 1, PROPELLANT:<1 (BUTYL ACETATE=1). FL PT:LIQUID:0F,-18C; PROPELLANT:-100F. FIRE FIGHT:IGNIT/EXPLO WHEN EXPOSED TO EXTREME HEAT. IF H*20 IS USED, FOG NOZZ ARE PREF. EXPLO HAZ:LIGHTS, OTHER FLAMES, SPKS, HEATERS, SMOKING, ELEC MOTORS/OTHER IGNIT SOURCES @ LOCATIONS DIST FROM MATL HNDLG POINT.

Transportation Data

Trans Data Review Date: 92141
 DOT PSN Code: DTJ
 DOT Symbol: D
 DOT Proper Shipping Name: CONSUMER COMMODITY
 DOT Class: ORM-D
 DOT Label: NONE
 IMO PSN Code: AIY
 IMO Proper Shipping Name: AEROSOL DISPENSERS
 IMO Regulations Page Number: 9022
 IMO UN Number: 1950
 IMO UN Class: 9
 IMO Subsidiary Risk Label: -
 IATA PSN Code: ALS
 IATA UN ID Number: 1950
 IATA Proper Shipping Name: AEROSOLS, 30, *
 IATA UN Class: 2.1

IATA Label: FLAMMABLE GAS
AFI PSN Code: ALS
AFI Prop. Shipping Name: AEROSOLS, NONFLAMMABLE, N.O.S.
AFI Class: FORB
AFI Basic Pac Ref: FORBIDDEN

=====
Disposal Data
=====

=====
Label Data
=====

Label Required: YES
Technical Review Date: 28FEB92
Label Date: 28FEB92
Label Status: G
Common Name: AEROSOL SPRAY PAINT FLUORESCENT, FL-7 GREEN
Chronic Hazard: YES
Signal Word: DANGER!
Acute Health Hazard-Moderate: X
Contact Hazard-Moderate: X
Fire Hazard-Severe: X
Reactivity Hazard-None: X
Special Hazard Precautions: EXTREMELY FLAMMABLE. ACUTE:VAPORS CAN CAUSE
NASAL/RESPIRATORY IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA,
HEADACHE, POSSIBLE UNCONSCIOUSNESS, EVEN ASPHYXIATION. CONTACT CAN CAUSE
SEVERE EYE IRRITATION, REDNESS, TEARING, BLURRED VISION, SKIN IRRITATION.
REPORTS HAVE ASSOCIATED RPTD/PRLNG OVEREXPOSURE TO SOLVENTS WITH PERMANENT
BRAIN & NERVOUS SYSTEM DAMAGE. HAS ALSO CAUSED LIVER ABNORMALITIES & DAMAGE
TO KIDNEYS, LUNGS, SPLEEN, HEART, ADRENALS IN LAB ANIMALS. DELIBERATE
INHALATION MAY BE HARMFUL OR FATAL.
Protect Eye: Y
Protect Skin: Y
Protect Respiratory: Y
Label Name: PLASTI-KOTE CO INC
Label Street: 1000 LAKE ROAD
Label City: MEDINA
Label State: OH
Label Zip Code: 44256
Label Country: US
Label Emergency Number: 216-725-4511