

MINWAX -- 2716 MINWAX WOOD FINISH DARK WALNUT
MATERIAL SAFETY DATA SHEET
NSN: 801000F035145
Manufacturer's CAGE: 0K1A4
Part No. Indicator: B
Part Number/Trade Name: 2716 MINWAX WOOD FINISH DARK WALNUT

=====
General Information
=====

Company's Name: MINWAX CO
Company's Street: 15 MERCEDES DRIVE
Company's P. O. Box: 438
Company's City: MONTVALE
Company's State: NJ
Company's Country: US
Company's Zip Code: 07645-5000
Company's Emerg Ph #: 201-391-0253/201-573-5700
Company's Info Ph #: 201-573-5700/201-391-0253
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: FE
Date MSDS Prepared: 02MAR95
Safety Data Review Date: 17JAN97
Preparer's Company: MINWAX CO
Preparer's St Or P. O. Box: 15 MERCEDES DRIVE
Preparer's City: MONTVALE
Preparer's State: NJ
Preparer's Zip Code: 07645-5000
MSDS Serial Number: CDCQK

=====
Ingredients/Identity Information
=====

=====
Physical/Chemical Characteristics
=====

Appearance And Odor: CLEAR AMBER TO OPAQUE EARTH-TONE, SLIGHTLY VISCOUS
LIQUID W/HYDROCARBON ODOR
Specific Gravity: 0.805-0.878
Solubility In Water: INSOLUBLE

=====
Fire and Explosion Hazard Data
=====

Flash Point: 106F
Flash Point Method: TCC
Extinguishing Media: WATER SPRAY, FOAM, DRY CHEMICAL/CO2
Special Fire Fighting Proc: DON'T USE A DIRECT STREAM OF WATER. PRODUCT
MAY BE REIGNITED ON SURFACE OF WATER. WEAR SCBA & PROTECTIVE CLOTHING. USE
WATERSPRAY TO COOL FIRE-EXPOSED CONTAINER
Unusual Fire And Expl Hazrds: CONTAINERS EXPOSED TO INTENSE HEAT FROM
FIRES SHOULD BE COOLED W/WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH
COULD RESULT IN CONTAINER RUPTURE.

=====
Reactivity Data
=====

Stability: YES
Cond To Avoid (Stability): USING/STORING NEAR HEAT, SPARKS, FLAME/OTHER
IGNITION SOURCES
Materials To Avoid: STRONG OXIDIZING AGENTS
Hazardous Decomp Products: HYDROCARBON FUMES, SMOKE, CO
Hazardous Poly Occur: NO

=====
Health Hazard Data
=====

Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: YES
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: SEE INGREDIENTS.
Signs/Symptoms Of Overexp: IRRITATION
Emergency/First Aid Proc: INHALATION: IMMEDIATELY REMOVE TO FRESH AIR.
SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: IMMEDIATELY FLUSH THOROUGHLY W/
WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL
ATTENTION IN ALL CASES.

=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: ABSORB W/SAND/OTHER SUITABLE ABSORBENT
MATERIAL & PLACE IN A CONTAINER FOR DISPOSAL. LARGE: AREA MAY BE SLIPPERY.
DIKE AROUND W/ABSORBENT. TRANSFER LIQUIDS & CONTAMINATED DIKING MATERIAL TO
SUITABLE CONTAINERS FOR RECOVERY/DISPOSAL.
Waste Disposal Method: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL
REGULATIONS.
Precautions-Handling/Storing: DON'T USE/STORE NEAR HEAT/SPARKS/OTHER
IGNITION SOURCES. CLOSE CONTAINER AFTER EACH USE. USE ONLY W/ADEQUATE
VENTILATION. KEEP OUT CHILDREN'S REACH.
Other Precautions: DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN & EYES.
AVOID INHALATION. IF USING INDOORS, OPEN ALL WINDOWS & DOORS TO MAKE SURE
THERE IS FRESH AIR MOVEMENT.

=====
Control Measures
=====

Respiratory Protection: REQUIRED
Ventilation: REQUIRED
Protective Gloves: RUBBER
Eye Protection: SAFETY GLASSES

=====
Transportation Data
=====

=====
Disposal Data
=====

=====
Label Data
=====