

Material Name: ACETYLENE, DISSOLVED SDS ID: MAT00280

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

ACETYLENE, DISSOLVED

Synonyms

ACETYLENE; ETHYNE; WELDING GAS; ACETYLEN; ETHINE; NARCYLEN; VINYLENE; UN 1001; C2H2;

Chemical Family

Hydrocarbons, aliphatic

Product Use

Industrial and Specialty Gas Applications.

Restrictions on Use

None known.

Details of the supplier of the safety data sheet

MATHESON TRI-GAS, INC.

150 Allen Road, Suite 302

Basking Ridge, NJ 07920

General Information: 1-800-416-2505

Emergency #: 1-800-424-9300 (CHEMTREC) Outside the US: 703-527-3887 (Call collect)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Gases - Category 1

Gases Under Pressure - Dissolved gas

Specific Target Organ Toxicity - Single Exposure - Category 3 (central nervous system.)

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

May cause drowsiness or dizziness.

May displace oxygen and cause rapid suffocation.

Precautionary Statement(s)

Prevention

Keep away from heat/sparks/open flame/hot surfaces - No smoking.

Use only outdoors or in a well-ventilated area.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Response

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.



SDS ID: MAT00280

Material Name: ACETYLENE, DISSOLVED

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Storage

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards

Rapid release of compressed gas may cause frostbite. Explosive with or without contact with air.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS					
CAS	Component Name	Percent			
74-86-2	ACETYLENE, DISSOLVED	100			

Section 4 - FIRST AID MEASURES

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Skin

Wash exposed skin with soap and water.

Eyes

Flush eyes with plenty of water.

Ingestion

If swallowed, get medical attention.

Most Important Symptoms/Effects

Acute

Frostbite, suffocation, Depression of central nervous system

Delayed

No information on significant adverse effects.

Note to Physicians

For inhalation, consider oxygen.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

carbon dioxide, regular dry chemical, Large fires: Use regular foam or flood with fine water spray.

Unsuitable Extinguishing Media

None known.

Special Hazards Arising from the Chemical

Severe explosion hazard. Vapor/air mixtures are explosive. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion.

Hazardous Combustion Products

Oxides of carbon.

Fire Fighting Measures

Move container from fire area if it can be done without risk. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn.

Page 2 of 8 Issue date: 2019-01-16 Revision 3.0 Print date: 2019-01-16



Material Name: ACETYLENE, DISSOLVED

Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Evacuate if fire gets out of control or containers are directly exposed to fire. Evacuation radius: 500 meters (1/3 mile). Consider downwind evacuation if material is leaking. Stop flow of gas.

SDS ID: MAT00280

Special Protective Equipment and Precautions for Firefighters

Wear personal protective clothing and equipment such as self-contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Avoid heat, flames, sparks and other sources of ignition. Stop leak if possible without personal risk. Reduce vapors with water spray. Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering. Notify Local Emergency Planning Committee and State Emergency Response Commission for release greater than or equal to RQ (U.S. SARA Section 304).

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight.

Subject to storage regulations: U.S. OSHA 29 CFR 1910.101.

Incompatible Materials

metals, halogens, oxidizing materials, metal carbide, reducing agents, halo carbons

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

ACETYLENE, DISSOLVED	74-86-2
ACGIH:	(See Appendix F: Minimal Oxygen Content, explosion hazard)
NIOSH:	2500 ppm Ceiling ; 2662 mg/m3 Ceiling

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Page 3 of 8 Issue date: 2019-01-16 Revision 3.0 Print date: 2019-01-16



SDS ID: MAT00280

Material Name: ACETYLENE, DISSOLVED

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Eye protection not required, but recommended.

Skin Protection

Protective clothing is not required.

Respiratory Protection

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

Glove Recommendations

Protective gloves are not required, but recommended.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Not available	Physical State	gas	
Odor	sweet odor	Color	colorless	
Odor Threshold	Not available	рН	Not available	
Melting Point	Not available	Boiling Point	Not available	
Boiling Point Range	Not available	Freezing point	Not available	
Evaporation Rate	Not available	Flammability (solid, gas)	Not available	
Autoignition Temperature	305 °C (581 °F)	Flash Point	Not available	
Lower Explosive Limit	2.5 %	Decomposition temperature	Not available	
Upper Explosive Limit	100 %	Vapor Pressure	760 mmHg @ -84 °C	
Vapor Density (air=1)	0.9	Specific Gravity (water=1)	Not available	
Water Solubility	0.94 % (@ 25 °C)	Partition coefficient: n- octanol/water	2691.53	
Viscosity	0.01 cp	Kinematic viscosity	Not available	
Solubility (Other)	Not available	Bioconcentration Factor (BCF)	3.48	
Density	1.1747 g/L at 0 °C	Henry's Law Constant	0.00277024 atm- m3/mole	
кос	4508.17 (estimated from water solubility)	Physical Form	gas	



Material Name: ACETYLENE, DISSOLVED

Sublimation	-84 °C (-119 °F)	Molecular Formula	Н-С-С-Н
Molecular Weight	26.04		

SDS ID: MAT00280

Solvent Solubility

Soluble

acetone, Benzene, chloroform, ether

Section 10 - STABILITY AND REACTIVITY

Chemical Stability

May decompose violently on heating. May explode when heated.

Possibility of Hazardous Reactions

Polymerizes with evolution of heat. Avoid contact with curing agents, accelerators, and/or initiators.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Containers may rupture or explode if exposed to heat.

Incompatible Materials

metals, halogens, oxidizing materials, metal carbide, reducing agents, halo carbons

Hazardous decomposition products

Oxides of carbon

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

nausea, vomiting, chest pain, wheezing, headache, drowsiness, dizziness, loss of coordination, bluish skin color, suffocation, lung congestion, coma

Skin Contact

rash

Eye Contact

no information on significant adverse effects

Ingestion

ingestion of a gas is unlikely

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and no selected endpoints have been identified.

Product Toxicity Data

Acute Toxicity Estimate

No data available.

Immediate Effects

Frostbite, suffocation, Depression of central nervous system

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

No data available.

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA.



SDS ID: MAT00280

Material Name: ACETYLENE, DISSOLVED

Germ Cell Mutagenicity

No data available.

Tumorigenic Data

No data available

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

Category 3. central nervous system

Specific Target Organ Toxicity - Repeated Exposure

Aspiration hazard

No data available.

Medical Conditions Aggravated by Exposure

No data available.

Additional Data

Stimulants such as epinephrine may induce ventricular fibrillation.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components.

Persistence and Degradability

No information available for the product.

Bioaccumulative Potential

No information available for the product.

Mobility

No information available for the product.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001. D003.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name: ACETYLENE, DISSOLVED

Hazard Class: 2.1 UN/NA #: UN1001 Required Label(s): 2.1

TDG Information:

Shipping Name: ACETYLENE, DISSOLVED

Hazard Class: 2.1 UN#: UN1001

Required Label(s): 2.1

International Bulk Chemical Code

This material does not contain any chemicals required by the IBC Code to be identified as dangerous chemicals in

bulk.

Page 6 of 8 Issue date: 2019-01-16 Revision 3.0 Print date: 2019-01-16



Material Name: ACETYLENE, DISSOLVED SDS ID: MAT00280

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this product's components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories

Flammable; Gas Under Pressure; Specific Target Organ Toxicity

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
ACETYLENE, DISSOLVED	74-86-2	Yes	Yes	Yes	Yes	Yes

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

Not listed under California Proposition 65.

Component Analysis - Inventory

ACETYLENE, DISSOLVED (74-86-2)

US	CA	AU	CN	EU	JP - ENCS	JP - ISHL	KR KECI - Annex 1	KR KECI - Annex 2
Yes	DSL	Yes	Yes	EIN	Yes	Yes	Yes	No

KR - REACH CCA	MX	NZ	PH	TH-TECI	TW	VN (Draft)
No	Yes	Yes	Yes	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 1 Fire: 4 Instability: 3

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes Updated: 05/01/2015 **Key / Legend**

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CA/MA/MN/NJ/PA -

California/Massachusetts/Minnesota/New Jersey/Pennsylvania*; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CFR - Code of Federal Regulations (US); CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EC – European Commission; EEC - European Economic Community; EIN - European Inventory of (Existing Commercial Chemical Substances); EINECS - European Inventory of Existing Commercial Chemical Substances Inventory; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; F - Background (for Venezuela Biological Exposure Indices); IARC - International Agency for Research on Cancer; IATA - International Air Transport

Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; ISHL - Japan Industrial Safety and Health Law; IUCLID - International Uniform Chemical Information Database; JP - Japan; Kow - Octanol/water partition coefficient; KR KECI Annex 1 - Korea Existing Chemicals Inventory (KECI) / Korea

 $Existing\ Chemicals\ List\ (KECL);\ KR\ KECI\ Annex\ 2\ -\ Korea\ Existing\ Chemicals\ Inventory\ (KECI)\ /\ Korea\ Existing\ Chemicals\ Inventory\ (KECI)\ /\ Korea\ Existing\ Chemicals\ Existing\$

Page 7 of 8 Issue date: 2019-01-16 Revision 3.0 Print date: 2019-01-16



Material Name: ACETYLENE, DISSOLVED

Existing Chemicals List (KECL), KR - Korea; LD50/LC50 - Lethal Dose/ Lethal Concentration; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIstsTM - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; MX – Mexico; Ne- Nonspecific; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; Nq - Non-quantitative; NSL – Non-Domestic Substance List (Canada); NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PEL- Permissible Exposure Limit; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH-Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; Sc - Semi-quantitative; STEL - Short-term Exposure Limit; TCCA – Korea Toxic Chemicals Control Act; TDG - Transportation of Dangerous Goods; TLV - Threshold Limit Value; TSCA - Toxic Substances Control Act; TW – Taiwan; TWA - Time Weighted Average; UEL - Upper Explosive Limit; UN/NA - United Nations /North American; US - United States; VLE - Exposure Limit Value (Mexico); VN (Draft) - Vietnam (Draft); WHMIS - Workplace Hazardous Materials Information System (Canada).

SDS ID: MAT00280

Other Information

Disclaimer:

Matheson Tri-Gas, Inc. makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Matheson Tri-Gas, Inc. shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

Page 8 of 8 Issue date: 2019-01-16 Revision 3.0 Print date: 2019-01-16