

UVR ELASTISEAL, S.B. YELLOW

Page: 3

MATERIAL SAFETY DATA SHEET

WASTE DISPOSAL METHOD

Dispose in accordance with local, state, and federal regulations including compliance with all regulations regarding spill reporting. Keep waste out of sewers, storm drains and surface waters.

----- SECTION VIII - SPECIAL PROTECTION INFORMATION -----

VENTILATION

Good general ventilation (Typically ten air changes per hour). When applicable provide sufficient ventilation to control vapors and to keep air contaminants below exposure limits.

RESPIRATORY PROTECTION

Atmospheric levels should be maintained below exposure limit. For normal operations an appropriate NIOSH/MSHA approved respirator for organic vapors should be worn if needed, or if product is used in a confined or poorly ventilated area.

EYE PROTECTION

Safety glasses with side shields or safety goggles. Contact lenses should not be worn when working with chemicals because they may contribute to the severity of an eye injury.

SKIN PROTECTION

Impervious gloves.

WORK/HYGIENIC PRACTICES

Good industrial hygiene practices should be followed. This includes preventing eye contact and minimizing skin contact. Eye wash station and safety shower should be available.

----- SECTION IX - SPECIAL PRECAUTIONS -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store in cool area out of direct sunlight. Do not store or use near heat, sparks or open flame. If product is supplied in pails or drums, keep closure tight during storage and when not in use. Pails and drums of this product should be grounded if poured or if transferred by pumping. Do not handle or use product until safety precautions have been read and understood.

OTHER PRECAUTIONS

Use this product with adequate ventilation. Avoid prolonged or repeated breathing of vapors. Empty containers can retain product residue so follow label warnings even after container is empty. Drums, pails and cans must not be washed out or used for other purposes. Drums should be completely emptied, properly bunged and promptly shipped to a drum reconditioner. All other containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Do not cut, weld, braze, solder, grind, or expose empty pails and drums to heat, sparks or other sources of ignition. Containers may explode resulting in injury or death.

----- SECTION X - ADDITIONAL INFORMATION -----

OSHA CLASSIFICATION:

29 CFR 1910.106(a) Parts 13 - 19, Flammable liquid - Class 1B

DOT CLASSIFICATION:

3, Flammable liquids, UN 1133

OTHER INFORMATION:

The information in section IV through IX is derived from the Material Safety Data sheets

UVR ELASTISEAL, S.B. YELLOW

Page: 4

M A T E R I A L S A F E T Y D A T A S H E E T

provided by our suppliers and to the best of our knowledge is correct. The user of a Dolphin product is responsible for establishing if the product is suitable for their particular application and assumes all risks for the use, handling and disposal of the product. The Dolphin Company, however, does warrant that our products meet our written specifications. There are no other warranties, expressed or implied including any warranty of "fitness for use". The exclusive remedy for all proven claims is replacement of our product and in no event shall The Dolphin Company be liable for incidental or consequential damages.

The information provided by the Dolphin Company in particular the information pertaining to the ingredients in our products is CONFIDENTIAL and PROPRIETARY! The recipient of this information is expected to protect its confidentiality and to take all steps necessary to prevent disclosure to a third party except as required by local, state and federal regulations.

UVR ELASTISEAL, S.B. YELLOW

Page: 1

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: UVR ELASTISEAL, S.B. YELLOW
 PRODUCT CODE: 6558

HMIS CODES: H P R
 2 3 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: DOLPHIN COMPANY
 ADDRESS : 922 LOCUST ST.
 TOLEDO, OH 43604

DATE REVISED : 12/19/96
 DATE PRINTED : 02/18/98
 NAME OF PREPARER : MR. LOWELL CHOCOLA

EMERGENCY PHONE : 419-241-8260
 INFORMATION PHONE : 419-241-8257

SECTION II - HAZARDOUS INGREDIENTS

REPORTABLE COMPONENTS AND EXPOSURE LIMITS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
* TOLUENE OSHA: PEL 100 PPM STEEL 150 PPM ACGIH: TLV 30 PPM LD50 (ORAL) 5000 MG/KG RAT LD50 (DERMAL) 14000 MG/KG RABBIT LC50 (INHALATION) 8000 PPM RAT VMSF NAPHTHA, RULE 66 ACGIH: TLV 300 PPM & STEEL 500 PPM	108-88-3	26 68 F	28
	64742-89-9	17.0 68 F	0.0

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of SARA and 40 CFR 372.

Any pigments and fillers in this product which may be considered "HAZARDOUS" are potentially hazardous ONLY if inhaled as an air-borne dust. Exposure by these ingredients as used in Dolphin's sealants, putties, bedding compounds and other non-sprayable products is highly unlikely.

SECTION III - PHYSICAL CHARACTERISTICS

BOILING POINT OR RANGE: 231 F - 262 F. SPEC. GRAVITY : 0.93
 VAPOR DENSITY: Heavier than air PERCENT SOLIDS : 63.00
 EVAPORATION RATE: Slower than ether V.O.C. : 3.00 lbs./gal.
 SOLUBILITY IN WATER: Not soluble
 APPEARANCE AND ODOR: Paste, mild solvent odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 45 - 50F. METHOD USED: ICC
 EXPLOSIVE LIMITS IN AIR BY VOLUME(%) - LOWER: 0.9 UPPER: 7

EXTINGUISHING MEDIA

Carbon dioxide (CO2), dry chemical, regular foam, alcohol foam, water fog or water spray.

SPECIAL FIREFIGHTING PROCEDURES

Self-contained breathing apparatus and protective clothing should be worn.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Decomposition and combustion products may be toxic.

