MINWAX -- 211 MINWAX WOOD FINISH PROVINCIAL MATERIAL SAFETY DATA SHEET NSN: 801000F009605 Manufacturer's CAGE: 0K1A4 Part No. Indicator: B Part Number/Trade Name: 211 MINWAX WOOD FINISH PROVINCIAL General Information Company's Name: MINWAX CO Company's Street: 15 MERCEDES DRIVE Company's P. O. Box: 438 Company's City: MONTVALE Company's State: NJ Company's Country: US Company's Zip Code: 07645-5000 Company's Emerg Ph #: 201-391-0253/201-573-5700 Company's Info Ph #: 201-573-5700/201-391-0253 Record No. For Safety Entry: 001 Tot Safety Entries This Stk#: 001 Status: FE Date MSDS Prepared: 02MAR95 Safety Data Review Date: 17JAN97 Preparer's Company: MINWAX CO Preparer's St Or P. O. Box: 15 MERCEDES DRIVE Preparer's City: MONTVALE Preparer's State: NJ Preparer's Zip Code: 07645-5000 MSDS Serial Number: CDCPZ Ingredients/Identity Information Physical/Chemical Characteristics Appearance And Odor: CLEAR AMBER TO OPAQUE EARTH-TONE, SLIGHTLY VISCOUS LIQUID W/HYDROCARBON ODOR Specific Gravity: 0.805-0.878 Solubility In Water: INSOLUBLE Fire and Explosion Hazard Data . Flash Point: 106F Flash Point Method: TCC Extinguishing Media: WATER SPRAY, FOAM, DRY CHEMICAL/CO2 Special Fire Fighting Proc: DON'T USE A DIRECT STREAM OF WATER. PRODUCT MAY BE REIGNITED ON SURFACE OF WATER. WEAR SCBA & PROTECTIVE CLOTHING. USE WATERSPRAY TO COOL FIRE-EXPOSED CONTAINER Unusual Fire And Expl Hazrds: CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED W/WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE. Reactivity Data Stability: YES

Cond To Avoid (Stability): USING/STORING NEAR HEAT, SPARKS, FLAME/OTHER

Materials To Avoid: STRONG OXIDIZING AGENTS

Hazardous Decomp Products: HYDROCARBON FUMES, SMOKE, CO

Hazardous Poly Occur: NO

Health Hazard Data 

Route Of Entry - Inhalation: YES Route Of Entry - Skin: NO Route Of Entry - Ingestion: YES Health Haz Acute And Chronic: SKIN: IRRITANT. INGESTION: HARMFUL/FATAL. Carcinogenicity - NTP: NO Carcinogenicity - IARC: YES Carcinogenicity - OSHA: NO Explanation Carcinogenicity: SEE INGREDIENTS. Signs/Symptoms Of Overexp: IRRITATION Emergency/First Aid Proc: INHALATION: IMMEDIATELY REMOVE TO FRESH AIR. SKIN: WASH THOROUGHLY W/SOAP & WATER. EYES: IMMEDIATELY FLUSH THOROUGHLY W/ WATER FOR 15 MINS. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES. Precautions for Safe Handling and Use Steps If Matl Released/Spill: ABSORB W/SAND/OTHER SUITABLE ABSORBENT MATERIAL & PLACE IN A CONTAINER FOR DISPOSAL. LARGE: AREA MAY BE SLIPPERY. DIKE AROUND W/ABSORBENT. TRANSFER LIQUIDS & CONTAMINATED DIKING MATERIAL TO SUITABLE CONTAINERS FOR RECOVERY/DISPOSAL. Waste Disposal Method: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS. Precautions-Handling/Storing: DON'T USE/STORE NEAR HEAT/SPARKS/OTHER IGNITION SOURCES. CLOSE CONTAINER AFTER EACH USE. USE ONLY W/ADEQUATE VENTILATION. KEEP OUT CHILDREN'S REACH. Other Precautions: DON'T TAKE INTERNALLY. AVOID CONTACT W/SKIN & EYES. AVOID INHALATION. IF USING INDOORS, OPEN ALL WINDOWS & DOORS TO MAKE SURE THERE IS FRESH AIR MOVEMENT. Control Measures Respiratory Protection: REQUIRED Ventilation: REQUIRED Protective Gloves: RUBBER Eye Protection: SAFETY GLASSES Transportation Data Disposal Data 

Label Data

http://siri.org/msds/h/q352/q393.html