

Fire Slip Inc

46-250
25-1
252

MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label) FIRE STICK MOUNTING LUBRICANT		GM COMMON CODE
MANUFACTURER'S NAME FIRE SLICK, INC.		EMERGENCY TELEPHONE NO. 704-821-6830
ADDRESS (Number, Street, City, State and Zip Code) 3491-D GRIBBLE RD: MATTHEWS, NC 28105		MANUFACTURER'S D-U-N-S NO.
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. (49 CFR 172.101) NONE		
ADDITIONAL HAZARD CLASSES (as applicable) NONE		
CHEMICAL FAMILY SODIUM SALT OF POLYACRYLIC ACID	FORMULA PROPRIETARY	

SECTION II — INGREDIENTS
(list all ingredients)

CAS REGISTRY NO.	%W	%V	CHEMICAL NAME(S)	Listed as a Carcinogen in NTP, IARC or OSHA 1910(z) (specify)
NONE	<5		POLYACRYLIC ACID	-
#1310-73-2	<1		SODIUM HYDROXIDE	-
NONE	<1		OCTYLPHENOXYPOLYETHOXYETHANOL	-

SECTION III — PHYSICAL DATA

BOILING POINT 212.4 °F 100°C	SPECIFIC GRAVITY (H ₂ O = 1)	1	
VAPOR PRESSURE (at 68 °F 20 °C) <input checked="" type="checkbox"/> mm Hg <input type="checkbox"/> psi	PERCENT VOLATILE BY VOLUME (%)	>95	PERCENT SOLID BY WEIGHT (%)
VAPOR DENSITY (AIR = 1)	EVAPORATION RATE (H ₂ O = 1)	1	<5
SOLUBILITY IN WATER	PH	9.3	
APPEARANCE AND ODOR BLUE VISCOUS LIQUID; NO ODOR	IS MATERIAL: GAS PASTE <input checked="" type="checkbox"/> LIQUID SOLID POWDER		

SECTION IV — FIRE AND EXPLOSION HAZARD DATA

FLASH POINT not combustible	FLAMMABLE LIMITS	LEL	UEL
EXTINGUISHING MEDIA NA			
SPECIAL FIRE FIGHTING PROCEDURES NA			
UNUSUAL FIRE AND EXPLOSION HAZARDS			

EFFECTS OF OVEREXPOSURE -- Conditions to Avoid		THRESHOLD LIMIT VALUE <input type="checkbox"/>
AVOID CONTACT WITH EYES		PERMISSIBLE EXPOSURE LIMIT <input type="checkbox"/>
		OTHER LIMIT <input type="checkbox"/>
PRIMARY ROUTES OF ENTRY Inhalation <input type="checkbox"/> Skin Contact <input type="checkbox"/> Other (specify) EYES		
EMERGENCY AND FIRST AID PROCEDURES		
MAY CAUSE MILD IRRITATION TO EYES - FLUSH WITH WATER - GET MEDICAL ATTENTION IF IRRITATION PERSISTS		

SECTION VI-REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	ACID
INCOMPATIBILITY (materials to avoid) ACID			
HAZARDOUS DECOMPOSITION PRODUCTS: NA			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	NONE

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED		PICOR MAY BE SLIPPERY, USE CARE
TO AVOID FALLING, DIKE AND ABSORB AND INERT MATERIAL.		
WASTE DISPOSAL METHOD DISPOSE ACCORDING TO LOCAL, STATE OR FEDERAL REGULATIONS		
CERCLA (Superfund) REPORTABLE QUANTITY (in lbs) NA		
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33) NA		
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water) NONE		
Theoretical _____ lb/gal	<input type="checkbox"/> Analytical _____ lb/gal	

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (specify type) NONE REQUIRED		
VENTILATION	LOCAL EXHAUST (Specify Rate) NONE REQUIRED	SPECIAL
	MECHANICAL (General) (Specify Rate)	OTHER
PROTECTIVE GLOVES (specify type) NONE REQUIRED		EYE PROTECTION (specify type) SAFETY GLASSES
OTHER PROTECTIVE EQUIPMENT NONE		

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	
NONE	
OTHER PRECAUTIONS NONE	